



HM1111C

17 lb. AVT® DEMOLITION HAMMER
Anti-Vibration Technology for
2X Less Vibration

- Powerful 14 AMP motor delivers 12.7 ft.lbs. of impact energy to handle the most demanding applications
- Anti-Vibration Technology is an internal counterbalance system that greatly reduces vibration for increased user comfort and greater productivity
- Detached rear handle is spring loaded to provide less vibration and more control
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs

Model HM1111C Includes: Side Handle (151769-0), Hammer Bit Grease (194683-7), CLOTH F/WIPING OIL (443122-7), 12" Bull Point, SDS-MAX (751423-A), Tool Case

Blows Per Minute (variable speed)	1,100 - 2,650 BPM
Impact Energy	12.7 ft.lbs. / 17.2 J
AMPS	14
Vibration (m/s ²)	8
Overall Length	20-3/4"
Net Weight	17.7 lbs.
Shipping Weight	28.6 lbs.
Bit Type	Accepts SDS-MAX



HM0870C

11 lb. DEMOLITION HAMMER
Compact Power with Less Weight

- Powerful 10 AMP motor delivers 8.4 ft.lbs. of impact energy to handle the most demanding applications
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- Soft start suppresses start-up reaction for better accuracy
- L.E.D. service light notifies the user approximately 8 hours before the brushes need to be replaced
- L.E.D. power light indicates switch failure or cord damage
- Variable speed control dial enables user to match the speed to the application for greater versatility

Model HM0870C Includes: Side Handle (135283-4), Hammer Bit Grease (194683-7), Tool Case

Blows Per Minute (variable speed)	1,100 - 2,650 BPM
Impact Energy	8.4 ft.lbs. / 11.4 J
AMPS	10
Vibration (m/s ²)	11
Overall Length	17-3/4"
Net Weight	11.1 lbs.
Shipping Weight	18.5 lbs.
Bit Type	Accepts SDS-MAX



HM0810B

11 lb. DEMOLITION HAMMER
Ideal for Light Chiseling, Chipping
and Scaling

- Compact with less weight for improved control
- Soft rubber grip side handle minimizes vibration and swivels 360° for operator convenience
- Innovative anti-vibration spring is positioned between tool body and rear handle for reduced operator fatigue
- One-touch tool retainer action for easy accessory installation and removal
- Makita Motor Advantage engineered for more power and longer tool life
- Extended life brushes are longer for more work between service intervals and less downtime

Model HM0810B Includes: Hex Wrench (783202-0), Tool Case

Blows Per Minute	2,900 BPM
Impact Energy	5.6 ft.lbs. / 7.6 J
AMPS	8.3
Vibration (m/s ²)	8
Overall Length	16-5/8"
Net Weight	12.8 lbs.
Shipping Weight	19.4 lbs.
Bit Type	3/4" Hex - 21/32" Round



HK1810

POWER SCRAPER
Versatile Tool for Scraping and
Tile Removal

- Air cushion hammering for longer tool life
- Quick change bit retainer for easy changes
- Automatic brush cut-off protects commutator from damage
- Factory grease packed for reduced maintenance
- All-ball bearing construction for longer tool life
- Accepts Makita Small bits

Model HK1810 Includes: 1-3/16" x 6" Scaling Chisel, Makita Small Shank (B-07331), 2" x 6" Scaling Chisel, Makita Small Shank (B-07347), 8-3/4" Bull Point, Makita Small Shank (B-06921), Dust Cover (423154-0), Tool Case

Blows Per Minute (variable speed)	0 - 3,200 BPM
Impact Energy	2.9 ft.lbs. / 3.9 J
AMPS	4.5
Vibration (m/s ²)	13.5
Overall Length	12-3/8"
Net Weight	7.1 lbs.
Shipping Weight	13.7 lbs.
Bit Type	Makita small

ROTARY HAMMERS



HR5212C

2" ADVANCED AVT® ROTARY HAMMER
Advanced Anti-Vibration Technology
for Significantly Less Vibration

- Powerful 15 AMP motor delivers 14 ft.lbs. / 19 J. of impact energy
- Advanced AVT® is an air actuated counterbalance, vibration absorbing housing and impact bolt damper spring that more effectively reduces vibration
- Electronic Controller is a feature package that provides constant speed control, soft start, soft no-load and variable speed

Model HR5212C Includes: Depth Rod, HR4013C (331955-1), Hammer Bit Grease (194683-7), Cloth F/Wiping Oil (443122-7), D-handle (417003-1), Straight Handle (454781-2) (454781-2), Straight Handle Assembly (135629-4) (135629-4), Accessory Case

AMPS	15
Capacities: Concrete Drilling	2"
Concrete Drilling w/ Core Bit	6-1/4"
Impact Energy	19 J / 14 ft.lbs.
Vibration (m/s ²)	9
Blows Per Minute (variable speed)	1,100 - 2,250 BPM
No Load Speed (variable speed)	130 - 260 RPM
Overall Length	23-1/2"
Cord Length (ft)	16.4'
Net Weight	26.2 lbs.
Shipping Weight	42 lbs.
Bit Type	Accepts SDS-MAX



HR4510C

1-3/4" AVT® ROTARY HAMMER
Anti-Vibration Technology for
2X Less Vibration

- Powerful 13.5 AMP motor delivers 9.2 ft.lbs. of impact energy to handle the most demanding applications
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- Soft start suppresses start-up reaction for increased accuracy
- L.E.D. service light notifies the user approximately 8 hours before the brushes need to be replaced
- L.E.D. power lights indicate switch failure or cord damage

Model HR4510C Includes: Side Handle (151769-0), D-handle (417003-1), Depth Gauge (321248-4), Hammer Bit Grease (194683-7), Tool Case

AMPS	13.5
Capacities: Concrete Drilling	1-3/4"
Concrete Drilling w/ Core Bit	5"
Impact Energy	12.5 J / 9.2 ft.lbs.
Vibration (m/s ²)	9.5
Blows Per Minute (variable speed)	1,250 - 2,750 BPM
No Load Speed (variable speed)	130 - 280 RPM
Overall Length	18"
Cord Length (ft)	16.4'
Net Weight	19.6 lbs.
Shipping Weight	35 lbs.
Bit Type	Accepts SDS-MAX



HR4013C

1-9/16" ADVANCED AVT® ROTARY HAMMER
Advanced Anti-Vibration Technology
for Significantly Less Vibration

- Powerful 11 AMP motor delivers 8.4 ft.lbs. / 11.4 J. of impact energy to handle the most demanding applications
- Advanced AVT® is an air actuated counterbalance, vibration absorbing housing and impact bolt damper spring that more effectively reduces vibration
- Electronic Controller is a feature package that provides constant speed control, soft start, soft no-load and variable speed

Model HR4013C Includes: D-Handle Assembly, HR4013C (196792-8), Depth Rod, HR4013C (331955-1), Side Handle Assembly (123138-5), Hammer Bit Grease (194683-7), Cloth F/Wiping Oil (443122-7), Accessory Case

AMPS	11
Capacities: Concrete Drilling	1-9/16"
Concrete Drilling w/ Core Bit	4-1/8"
Impact Energy	11.4 J / 8.4 ft.lbs.
Vibration (m/s ²)	5
Blows Per Minute (variable speed)	1,450 - 2,900 BPM
No Load Speed (variable speed)	250 - 500 RPM
Overall Length	18-11/16"
Cord Length (ft)	15.6'
Net Weight	15.1 lbs.
Shipping Weight	27.8 lbs.
Bit Type	Accepts SDS-MAX



HR4002

1-9/16" ROTARY HAMMER
Sequential Impact Timing for Up to
50% Faster Drilling

- Powerful 10 AMP motor delivers 4.6 ft.lbs. of impact energy
- 2-mode operation for "Hammering Only" or "Hammering with Rotation"
- Rubberized ergonomic soft grip provides more comfort
- "No hammering when idling" functions helps increase tool life
- One-touch sliding chuck for quick bit changes
- Torque limiting clutch engineered to prevent gear damage by automatically disengaging gears if the bit binds

Model HR4002 Includes: Side Handle (158131-0), Depth Gauge (321248-4), Hammer Bit Grease (194683-7), Tool Case

AMPS	10
Capacities: Concrete Drilling	1-9/16"
Concrete Drilling w/ Core Bit	4-1/8"
Impact Energy	6.2 J / 4.6 ft.lbs.
Vibration (m/s ²)	17.5
Blows Per Minute	2,500 BPM
No Load Speed	680 RPM
Overall Length	18"
Cord Length (ft)	9.8'
Net Weight	14.6 lbs.
Shipping Weight	26.89 lbs.
Bit Type	Accepts SDS-MAX