

C
Ultra Thin Cut-Off Wheels
FASTER CUTTING 20% Thinner Than Most Competitor Wheels.

Zirconia aluminum construction makes these wheels ideal for ferrous metals including stainless steel

Ultra thin design requires less energy for improved battery life when used with cordless grinders

60 grit abrasive for cleaner cuts


SPEED


.032" thick for faster cutting and reduced material waste

Ultra Thin Cut-Off Wheels

	Diameter	Thickness	Arbor	Grit	Max. RPM	Model	1/Pkg. Part #	25/Pkg. Part #
Flat Center	4"	.032"	5/8"	60	15,300	GA4030	B-46143	B-46143-25
• .032" thick for faster cutting and reduced material waste	4-1/2"	.032"	7/8"	60	13,300	9557NB/PB, 9564CV/PC/P, GA4530, GA4534, XAG01, XAG03, XAG06	B-46159	B-46159-25
	5"	.032"	7/8"	60	12,250	9005B/BZ, 9558PB, 9565CV/PC, GA5010Z, GA5020/Y	B-46165	B-46165-25

Depressed Center

- For making cuts in metal and stainless steel pipes, sheet, and channel



	4-1/2"	.032"	7/8"	60	13,300	9557NB/PB, 9564CV/PC/P, GA4530, GA4534, XAG01, XAG03, XAG06	A-96431	A-96431-25
	5"	.032"	7/8"	60	12,250	9005B/BZ, 9558PB, 9565CV/PC, GA5010Z, GA5020/Y	A-96447	A-96447-25

C
Flex & Cut-Off Wheels
Super Thin Cut-Off Wheels

	Diameter	Thickness	Arbor	Grit	Max. RPM	Model	Stainless 25/Pkg. Part #	Metal 25/Pkg. Part #
	4"	3/64" / .045"	5/8"	46	15,280	GA4030	724111-A-25	724114-A-25
	4-1/2"	3/64" / .045"	7/8"	46	13,285	9557NB/PB, 9564CV/PC/P, GA4530, GA4534, XAG01, XAG03, XAG06	724112-A-25	724115-A-25
• Super thin design lasts up to 3.5x longer than standard cut-off wheels	5"	3/64" / .045"	7/8"	46	12,200	9005B/BZ, 9558PB, 9565CV/PC, GA5010Z, GA5020/Y	724113-A-25	724116-A-25
• Engineered for less heat discoloration, less material removal, and less burring for a better finish	6"	1/16" / .060"	7/8"	46	10,185	9566CV/PC, GA6010Z, GA6020	724118-A-25	724117-A-25

Cut-Off Wheels

	Diameter	Thickness	Arbor	Grit	Max. RPM	Model	Bulk Shelf Pack Qty.	Metal Bulk* Part #	Metal 10/Pkg. Part #	Masonry 10/Pkg. Part #
	4"	3/32" / .090"	5/8"	36	13,600	GA4030	25	A-90358 *Must be ordered in shelf pack quantity	724107-5-10	724104-1-10
	4"	5/64" / .080"	5/8"	46	14,000					
	4"	3/32" / .090"	5/8"	36	15,000					
• For all ferrous materials, steel, and cast iron										
• For masonry/concrete, marble, slate, and more										

Flex Wheels

	Diameter	Thickness	Arbor	Grit	Max. RPM	Model	10/Pkg. Part #	25/Pkg. Part #
	4"	1/8"	5/8"	46	13,700	GA4030	741404-OBP	
	4"	1/8"	5/8"	60	13,700		741404-0CP	
• Improved material removal with less noise and vibration for improved efficiency	NEW 4-1/2"	5/32"	7/8"	36	13,300	9557NB/PB, 9564CV/PC/P, GA4530, GA4534, XAG01, XAG03, XAG06		A-97411-25 (Stainless – INOX)
• Flexible design allows for more surface area contact and more efficient material removal								

Warning: Consult owner/operator manual and adhere to all safety precautions for accessory items. Always use recommended guards. Failure to do so may result in serious injury or death from exploding wheels. Refer to ANSI B7.1 and owner/operator manual for proper accessory mounting and grinding procedures. Always wear eye protection that meets ANSI Z87.1 requirements plus a face shield wherever possible. Tools must always be properly guarded.