SPECIFICATIONS – MicroTouch Control

Construction………………………………… 6061 Billet Aluminum
Display…………………………… 16 LED Temperature Display
Interface…………………………. 3 Capacitive Touch Buttons
Communication………………………….. ThermaSol CAN Bus
Supply Voltage………………………………………………….. 5V DC

Contemporary

Basic Functions:
- Recall last steam settings
- Turn steam system on or off
- Set desired steam shower temperature
- Operate PowerFlush™ cleaning system
- Diagnostic LEDs, display troubleshooting errors codes
- Patent Pending Infrared temperature sensing
- Smooth operation with capacitive touch technology (CTT)

Installation Notes:
The control should be installed 60" inches from the floor of the shower, inside the shower only, and away from the steam head.

Finish Chart:
Select desired finish and replace XXX with code.

PC = Polished Chrome	PN = Polished Nickel
SC = Satin Chrome	SN = Satin Nickel
PB = Polished Brass	BN = Black Nickel
SB = Satin Brass	AN = Antique Nickel
AB = Antique Brass	PG = Polished Gold
COP = Polished Copper	ORB = Oil Rubbed Bronze
ACOP = Antique Copper	WHT = White

Product Specification:
The user interface control shall be 2.9" Dia x .63" in dimension. The Control shall be made from billet aluminum and includes the ability to operate and control: Smart Steam and PowerFlush™ System, using 100% networked digital technology.

Shipping Information:

Weight…………… 4 lbs.
Length………………12 in.
Width……………….12 in.
Height………………6 in.

Styling Information:
The control is shown in Contemporary

Contemporary
Edge

For any further assistance please contact
ThermaSol at 800.776.0711 or
sales@thermasol.com

Ø2.900

.63