

## CONTACTOR REPLACEMENT



### SureSwitch Contactor Replacement

- Up to five times longer life compared to traditional mechanical contactors
- Microprocessor control nearly eliminates contact welding and pitting
- Sealed to keep out ants and debris
- Protects compressor from brownouts and short cycling
- Short cycle protection, 0 or 180 seconds (selectable)
- Tricolor diagnostic LED displays
- Zero chatter latching relay
- Random start delay on power up and brownout recovery
- Compressor test and cycle count by pushbutton
- Four-hole mounting matches mechanical contactors

**White  
Rodgers**

PART NO	COIL VOLTAGE (VAC)	MOTOR FLA RATING AT 230V (A)	MOTOR LRA RATING AT 230V (A)
49P11-843	24	30	150


## CONTROL RELAYS



### CONTROL RELAYS – SEALED CASE


**PROTECH**

#### Control Relays – Sealed Case (SPST-NO)




PART NO	CONTACT BIAS	COIL VOLTAGE (VAC)	FLA @120V (A)	FLA @230V (A)	LRA @120V (A)	LRA @230V (A)
42-25104-01	NO	24	12	8	60	48
42-21571-08	NO	24	12	8	60	48
42-25104-02	NO	208, 230	12	8	60	48
42-101208-02	NO	208, 230	12	8	60	48
42-25104-09	NO	120	12	8	60	48

#### Control Relays – Sealed Case (SPDT)




PART NO	CONTACT BIAS	COIL VOLTAGE (VAC)	FLA @120V (A)	FLA @230V (A)	LRA @120V (A)	LRA @230V (A)
42-25104-07	NO / NC	120	14	8	84	48
90295Q	NO / NC	208, 230	—	8	—	18
42-25104-08	NO / NC	230	14	8	84	48
42-25104-06	NO / NC	24	14	8	84	48

#### Control Relays – Sealed Case (DPST-NO/NC)



PART NO	CONTACT BIAS	COIL VOLTAGE (VAC)	FLA @120V (A)	FLA @230V (A)	LRA @120V (A)	LRA @230V (A)
42-25104-04	NC / NO	120	12	8	60	48
PD425117	NC / NO	24	12	8	60	48
42-25104-03	NC / NO	24	12	8	60	48

#### Control Relays – Sealed Case (DPST-NO/NO)



PART NO	CONTACT BIAS	COIL VOLTAGE (VAC)	FLA @120V (A)	FLA @230V (A)	LRA @120V (A)	LRA @230V (A)
42-101754-01	NO / NO	120	1	2-1/2	25.3	110