




FLASHING

Round Flashing Galvanized - 6FFU12

Round Flashing Aluminum - 6PL-AFFU12

- Available in galvanized and aluminum models flat to 6/12 pitch (Standard), as well as for steeper pitches of 7/12 to 12/12, 13/12 to 18/12, and 19/12 to 24/12.


Tall Cone Flashing

- Used for flat to 1/12 pitch roofs, as well as on flat roofs in snowpack areas to reduce chances of leakage

PART #	SIZE	PITCH	(A) SKIRT	METAL
6F 6PL-AF	6"	Std. Flat to 6/12	4"	Galvanized Aluminum
8F 8PL-AF	8"	Std. Flat to 6/12	4"	Galvanized Aluminum
6FFU 6PL-AFFU	6"	Flat to 6/12	6"	Galvanized Aluminum
8FFU 8PL-AFFU	8"	Flat to 6/12	6"	Galvanized Aluminum
6FFU12 6PL-AFFU12	6"	7/12 to 12/12	6"	Galvanized Aluminum
8FFU12 8PL-AFFU12	8"	7/12 to 12/12	6"	Galvanized Aluminum
6FFU18 6PL-AFFU18	6"	13/12 to 18/12	6"	Galvanized Aluminum
8FFU-18 8PL-AFFU18	8"	13/12 to 18/12	6"	Galvanized Aluminum
6FFU24 6PL-AFFU24	6"	19/12 to 24/12	6"	Galvanized Aluminum
8FFU24 8PL-AFFU24	8"	19/12 to 24/12	6"	Galvanized Aluminum

PART #	SIZE	A	B
6FT	6"	4" on 4 sides	12"
8FT	8"	4" on 4 sides	12"

ADAPTER
PART # SIZE


6SWA	6"
8SWA	8"

Stovepipe Adapter

- Included in a ceiling support assembly, roof support assembly, and tee assembly for easier installation of single-wall connector pipe