

Forced Air Propane Comparison Chart



Model#	MH38QFA	MH60QFAV	MH85QFAV	MH125QFAV	MH170QFAVT	MH400FAVT
Stock#	F271350	F271370	F271380	F271390	F271400	F272425
UPC	089301713505	089301713703	089301713802	089301713901	089301714007	089301724259
BTU Rating	38,000	30,000 / 60,000	50,000 / 85,000	75,000 / 125,000	125,000 / 175,000	250,000 / 400,000
Variable Output	NO	YES	YES	YES	Thermostat YES	Thermostat YES
Heats Up To: (Approx. Sq. Ft.)	950	1,500	2,125	3,125	4,250	10,000
Minimum Recommended Tank Size	20 lb.	20 lb.	20 lb.	40 lb.	100 lb.	(2X) 100 lb.
Approx. Run Time On Minimum Tank Size	12 Hrs.	7 Hrs. High 14 Hrs. Low	5 Hrs. High 8.5 Hrs. Low	7 Hrs. High 11.5 Hrs. Low	12.5 Hrs. High 17 Hrs. Low	10 Hrs. High 17 Hrs. Low
Ignition	Piezo	Continuous	Continuous	Continuous	Automatic Solid State	Automatic Solid State

FORCED AIR PROPANE HEATERS

- 10' hose & regulator included
- Operates on propane
- Certified
- Patented quiet burner technology
- Runs 50% quieter than standard forced air heaters



COMMON USES

- Construction sites
- Garages

TWO TANK HOOK UP KIT

Stock # - F273737
UPC - 089301737372

(30" Hose Assembly with Excess Flow Soft Nose POL's on both ends x Full Flow Tee)
- Most commonly used to hook multiple bulk tanks to most applications.

