drinking water cartridges



W5CIP478

carbon impregnated cellulose

- ★ Economically priced
- ★ Dual purpose cartridge provides bad taste, odor, and chlorine taste & odor reduction, as well as sediment filtration*
- ★ Design maximizes dirt holding capacity
- ★ For municipal/chlorinated water (not recommended for well water applications)
- ★ Recommended for point of use filtration

NSF

The W5CIP is Tested and Certified by NSF International.



WGC478

granular activated carbon (GAC)

- ★ Effective taste, odor, and chlorine taste & odor reduction
- ★ Cartridge design ensures that water passes through the entire length of the carbon bed, maximizing contact time.
- ★ Reduces particles as small as 20-micron in size by mechanical means



W.5CB

carbon block cartridges

- ★ Excellent for bad taste, odor, and chlorine taste & odor reduction*
- ★ Specialty blocks are capable of reducing lead and certain volatile organic compounds (VOCs)*
- ★ NSF/ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means.

NSF

The W.5CB and WLC-R are Tested and Certified by NSF International.

			housings																
	Drinking Water	Micron Rating †	3/8" SlimLine® Housings	W385-PR (5")	W38-PRA (10")	W38-PRB (10")	W38-PRQC (10")	3/4" Standard Housings	W34-PR (10")	WC34-PRB (10")	WC34-PR (10")	WVC34 (10")	W34-PRB (10")	3/4" High Temp Housing	WH34 (10")	3/4" Stainless Steel	ST-1 (10")	ST-2 (20")	ST-3 (30")
cartridges	Filter Cartridge		Flow Rate* (gpm)																
	W.5CB478	0.5		1															
	W5CIP478	5		1															
	WGC478	—		1															
	W.5CB	0.5			1	1	1												
	WLC-R	0.5			0.6	0.6	0.6												
	W5CIP	5			5	5	5		5	5	5	5	5		5		5	10	15
	WCC	—			1	1	1												

† Micron raitings are nominal
** Flow rates are calculated for cartridges according to the housing in which they are being used*

Model	Part	Medium	Micron Rating (nominal)	Max. Flow Rate (gpm)	Diameter	Length
Carbon Impregnated Cellulose - reduces particles as small as 5 micron in size by mechanical means						
W5CIP478	155022-52	Carbon Impregnated Cellulose	5	2	2-1/2"	4-7/8"
W5CIP	155002-52	Carbon Impregnated Cellulose	5	5	2-5/8"	9-3/4"

Model	Part	Medium	Chlorine Taste & Odor Reduction @ Flow Rate**	Max. Flow Rate (gpm)	Diameter	Length
Granular Activated Carbon (GAC)						
WGC478	155110-51	Granular Activated Carbon	>750 Gal. @ 0.5 GPM	1	2-7/8"	4-7/8"
WCC	155155-51	Granular Activated Coconut Carbon	>500 Gal. @ 1 GPM	1	2-7/8"	9-3/4"

Model	Part	Medium	Reduces**	Micron Rating (nominal)	Chlorine Taste & Odor Reduction @ Flow Rate**	Lead (gallons)	VOCs (gallons)	Max. Flow Rate	Diameter	Length
Carbon Block - reduces particles as small as 5 micron in size by mechanical means										
W.5CB478	155169-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cyst	0.5	>3,000 Gal. @ 1 GPM	N/A	N/A	1	2-7/8"	4-7/8"
W.5CB	155162-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cyst	0.5	>20,000 Gal. @ 1 GPM	N/A	N/A	1	2-7/8"	9-3/4"
WLC-R	155268-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cyst, Lead & VOC	0.5	>20,000 Gal. @ 0.6 GPM	600**	300**	0.6	2-7/8"	9-3/4"