



Faucet Specifications

Color	SKU
PVD steel	401991

Product Features

- Insulated pull-down handspray with dual spray patterns
- 360° swivel provides extended range
- Magnetized handspray holder for ease of use
- Flexible spring allows easy range of motion
- Ceramic disc cartridge
- 1.5 GPM (Gallons Per Minute) flow rate

Planning information

All BLANCO faucets require the same size, 1 # diameter drilled faucet hole. All faucet parts required for installation are included.

ASME A112.18.1/CSA B125.1, NSF/ANSI/CAN 61, NSF/ANSI 372 listed

AB 1953, CalGreen, George SB 370 compliant



Warranty

BLANCO offers a limited lifetime warranty on all sinks and faucets, as well as a one-year warranty on all custom accessories.

Code/Standards Compliance

BLANCO sinks and faucets are third-party tested and certified to standards and listed by applicable certification bodies. For more information on individual product listings, contact our office or listing organization.



View our how-to videos to learn more about installing and caring for BLANCO products:

<https://www.blanco.com/us-en/service/how-to-videos/how-to-videos-for-sinks/>

Questions? Contact us today



BLANCO America, Inc.
110 Mount Holly By-Pass
Lumberton, NJ 08048

Phone & Fax
Phone: 888-668-6201
Fax: 609-668-6211

While BLANCO endeavors to provide accurate information, all dimensions are nominal, cannot be guaranteed, and are subject to change or cancellation. BLANCO assumes no responsibility for use of superseded or voided specifications.