

LA-CO® T-O-T® Pipe Thread Compound

- Pressures: 350 PSI (24 BAR) gas; 500 PSI (34 BAR) liquid
- Sealing temperature: up to 350°F (177°C)
- No-drip formula for fast application on metal threads
- Lead-free, non-toxic, no V.O.C.'s
- DO NOT USE ON OXYGEN SERVICE



| ITEM NO. | DESCRIPTION | STD QTY | U M |
|----------|-------------------------------------|---------|-----|
| 17263 | [12219] 8 oz. Pipe Compound (B-I-C) | 24 | EA |

Oatey® Gray Pipe Joint Compound

- Soft-setting compound does not harden
- Use on water, air and steam pipe lines
- Not for use on plastic threads
- Gas pressure to 3,000 PSI at -20° F to 400° F
- Liquid pressure to 10,000 PSI at -20° F to 500° F



| ITEM NO. | DESCRIPTION | STD QTY | U M |
|----------|-----------------------------------|---------|-----|
| 17895 | [31228] 8 oz. Pipe Joint Compound | 12 | EA |

LA-CO® Slic-Tite® Paste With PTFE

- Contains PTFE for greater sealing power
- Pressures: 3,000 PSI (204 BAR) gas; 10,000 PSI (680 BAR) liquid
- Sealing temperature: -50°F to 500°F (-46°C to 260°C)
- Can be used on a variety of metals and plastic
- Can be used with Natural Gas
- DO NOT USE ON OXYGEN SERVICE



| ITEM NO. | DESCRIPTION | STD QTY | U M |
|----------|---|---------|-----|
| 17268 | [42002] 1.5 oz. Slic-Tite Paste (Display) | 24 | EA |
| 16143 | [42009] 4 oz. Slic-Tite Paste (B-I-C) | 24 | EA |
| 16144 | [42019] Slic-Tite Paste 1/2 pt (B-I-C) | 24 | EA |
| 16145 | [42029] Slic-Tite Paste 1 pt (B-I-C) | 24 | EA |
| 17261 | [42013] Slic-Tite Paste 1 qt | 12 | EA |

LA-CO® Slic-Tite® Stik® With PTFE

- Pressures: 500 PSI (34 BAR) for gas; 5,000 PSI (340 BAR) for liquid
- Sealing temperature: -50°F to 350°F (-46°C to 177°C)
- Contains PTFE particles for greater sealing power
- Washes off hands and clothes easily; quick and easy cleanup
- Safe, non-toxic, non-drying
- DO NOT USE ON OXYGEN SERVICE
- Made in U.S.A.
- For use on/with metal and PVC



| ITEM NO. | DESCRIPTION | STD QTY | U M |
|----------|---------------------------------|---------|-----|
| 16146 | [41600] Slic-Tite Stik 1-1/4 oz | 24 | EA |

Oatey® Pipe Joint Compound With PTFE

- Lubricates & seals all threaded joints
- White, non-hardening, non-separating, non-toxic paste
- Withstands up to 3,000 PSI on gases from -50° to +400°F
- Withstands 10,000 PSI on liquids from -50° to +500°F
- Use with water, steam, caustics or dilute acid lines of PVC, CPVC, ABS, cyclocac, polypropylene, iron, steel or copper



| ITEM NO. | DESCRIPTION | STD QTY | U M |
|----------|--------------------------------------|---------|-----|
| 17897 | [31230] 4 oz. Joint Compound w/ PTFE | 12 | EA |
| 17898 | [31231] 8 oz. Joint Compound w/ PTFE | 12 | EA |

LA-CO® Plasto-Joint Stik®

- Pressures: 300 PSI (20 BAR) gas; 500 PSI (34 BAR) liquid
- Sealing temperature: up to 250°F (121°C)
- DO NOT USE ON OXYGEN SERVICE
- For use on/with ABS, PVC, and CPVC
- Made in U.S.A.



| ITEM NO. | DESCRIPTION | STD QTY | U M |
|----------|-------------------------------------|---------|-----|
| 16152 | [11775] 1-1/4 oz. Plasto Joint Stik | 144 | EA |

Mechanics Gloves See Page 119



- Synthetic leather
- Reinforced palm
- Black spandex back
- Velcro closure



- Pig grain leather
- Thinsulate lining
- Reinforced palm
- Blue spandex back
- Velcro closure



- Synthetic leather
- Reinforced palm
- Hi-viz orange back
- TPR padding
- Velcro closure