

**INFORMATION**  
A,B,O, SECTION

1. Bores  $\frac{5}{8}$ ",  $\frac{3}{4}$ ",  $\frac{7}{8}$ ", indicated by (•k) have standard  $\frac{3}{16}$ " x  $\frac{3}{32}$ " keyways.
2. Bores over  $\frac{7}{8}$ ", indicated by (•k) have  $\frac{1}{4}$ " x  $\frac{1}{8}$ " keyway.
3. Special bores, keyways, set screws can be had at a slight increase in price with production quantities.


**A SECTION**

For 4L or 1/2" x 11/32" belts.



**B SECTION**


For 5L or 2 1/32" x 7/16" belts.



Hub size dimension of largest bore size. Dimensions are approximate.

**O SECTION**

For 3L or 3/8" x 1/4" belts.



**HUBLESS A SECTION**

For 4L or 1/2" x 11/32" belts.



**SINGLE "V" GROOVED PULLEYS**

Stock No.	Outside Diam.	Pitch Diam.	Diameter of Bore							No. of Spokes	Net Wt. Ozs.	W	F	H
			1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"					
150-A	1 1/2"	1.25"			•	•	•			0	2.3	1 1/8"	1 1/16"	1 5/16"
175-A	1 3/4"	1.5"			•	•	•k	•k		0	4.0	1 1 1/64"	1 1/16"	1 3/8"
200-A	2"	1.75"			•	•	•k	•k		0	4.0	1 1/16"	1 1/16"	1 1/4"
225-A	2 1/4"	2"			•	•	•k	•k		0	5.7	1 7/32"	1 1/16"	1 1/2"
250-A	2 1/2"	2.25"			•	•	•k	•k		0	8.0	1 7/32"	1 1/16"	1 1/2"
275-A	2 3/4"	2.5"			•	•	•k	•k		0	7.0	1 7/32"	1 1/16"	1 1/2"
300-A	3"	2.75"			•	•	•k	•k		0	9.2	1 7/32"	1 1/16"	1 1/2"
325-A	3 1/4"	3"			•	•	•k	•k		0	9.6	1 7/32"	1 1/16"	1 1/2"
350-A	3 1/2"	3.25"			•	•	•k	•k		0	11.0	1 7/32"	1 1/16"	1 1/2"
400-A	4"	3.75"			•	•	•k	•k		0	13.2	1 7/32"	1 1/16"	1 1/2"
450-A	4 1/2"	4.25"			•	•	•k	•k		0	15.5	1 7/32"	1 1/16"	1 1/2"
500-A	5"	4.75"			•	•	•k	•k	•k	0	17.0	1 7/32"	1 1/16"	1 1/2"
550-A	5 1/2"	5.25"			•	•	•k	•k	•k	4	14.5	1 9/16"	1 1/16"	1 3/8"
600-A	6"	5.75"			•	•	•k	•k	•k	3	16.0	1 5/16"	1 1/16"	1 13/64"
700-A	7"	6.75"			•	•	•k	•k	•k	6	20.0	1 5/16"	1 1/16"	1 13/64"
800-A	8"	7.75"			•	•	•k	•k	•k	6	21.0	1 5/16"	1 1/16"	1 13/64"
900-A	9"	8.75"			•	•	•k	•k	•k	6	25.0	1 5/16"	1 1/16"	1 13/64"
1000-A	10"	9.75"			•	•	•k	•k	•k	6	28.3	1 5/16"	1 1/16"	1 13/64"
1100-A	11"	10.75"			•	•	•k	•k	•k	6	31.0	1 5/16"	1 1/16"	1 13/64"
1200-A	12"	11.75"			•	•	•k	•k	•k	6	33.0	1 5/16"	1 1/16"	1 13/64"
1400-A	14"	13.75"			•	•	•k	•k	•k	6	42.0	1 5/16"	1 1/16"	1 13/64"

All above "A" section pulleys have hollow head set screws and are supplied as follows:  
1) Packaged in individual cartons. 2) Shipped in bulk lots.

Stock No.	Outside Diam.	Pitch Diam.	Diameter of Bore							No. of Spokes	Net Wt. Ozs.	W	F	H
			1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"					
200-B	2"	1.5"			•	•k				0	5.0	1 3/8"	1 3/16"	1 3/32"
250-B	2 1/2"	2"			•	•k	•k			0	7.0	1 1/4"	1 3/16"	1 1/8"
300-B	3"	2.5"			•	•k	•k			0	10.0	1 5/16"	1 3/16"	1 1/8"

All the above "B" section pulleys have hollow head set screws and are supplied as follows:  
1) Packaged in individual cartons. 2) Shipped in bulk lots.

Stock No.	Outside Diam.	Pitch Diam.	Diameter of Bore							No. of Spokes	Net Wt. Ozs.	W	F	H
			1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"					
100-O	1"	.9"			•					0	1.0	7/8"	1/2"	3/4"
150-O	1 1/2"	1.4"	•		•					0	2.5	1"	1/2"	5/16"
200-O	2"	1.9"	•		•					0	4.0	1"	1/2"	1"
250-O	2 1/2"	2.4"			•					0	5.25	1"	1/2"	1 1/8"
300-O	3"	2.9"			•					0	6.5	1"	1/2"	1 1/8"
350-O	3 1/2"	3.4"			•					0	8.5	1"	1/2"	1 1/8"
400-O	4"	3.9"			•					0	10.0	1"	1/2"	1 1/8"

All "O" section single grooved pulleys have hollow head set screws and are supplied in standard die cast finish and shipped in bulk lots.

Stock No.	Outside Dia.	Pitch Diam.	Diameter of Bore							No. of Spokes	Net Wt. Ozs.	W	F	H
			1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"					
H-200-A	2"	1.75"			•					0	3.0	43/64"		
H-250-A	2 1/2"	2.25"			•	•k	•k			0	5.0	5/8"		
H-300-A	3"	2.75"			•	•k	•k			0	6.0	5/8"		

All hubless pulleys have hollow head set screws and are supplied in Standard die cast finish and shipped in bulk lots. Use side by side for multiple drives.  
Bore Size Identification No. 1/4"-1, 5/16" - 2, 3/8" - 3, 1/2" - 5, 5/8" - 6, 3/4" - 7, 1" - 8