


**PEX-a Tubing Coils with O₂ Barrier
94000 Series**

High molecular cross-linked polyethylene (PEX-a) with minimum bending radii of 6× the diameter at 68°F (20°C). Maximum operating temperature: 180°F @ 100 PSI (82°C @ 690 kPa). Covered by a twenty-five year manufacturer's limited warranty. Comes with oxygen diffusion barrier which prevents oxygen from entering the heating system through the tubing wall.

For complete specifications, see submittal [SUB94000](#).

Stk#	Description	Pkg Qty	Skid Qty	Unit	List Price / Unit
94205	½" 250ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	48	coil	\$ 273.91
94305	½" 300ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	48	coil	\$ 328.68
94505	½" 500ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	32	coil	\$ 547.83
94105	½" 1000ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	16	coil	\$ 1,095.64
94319	⅝" 300ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	32	coil	\$ 444.72
94519	⅝" 500ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	16	coil	\$ 741.20
94119	⅝" 1000ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	12	coil	\$ 1,482.37
94322	¾" 300ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	16	coil	\$ 564.59
94522	¾" 500ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	12	coil	\$ 940.98
94122	¾" 1000ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	7	coil	\$ 1,881.96
94128	1" 100ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	28	coil	\$ 329.30
94528	1" 500ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	7	coil	\$ 1,646.48
94135	1-¼" 100ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	12	coil	\$ 530.39
94335	1-¼" 300ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	7	coil	\$ 1,591.18
94141	1-½" 100ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	10	coil	\$ 736.57
94341	1-½" 300ft O ₂ Barrier HeatLink® UV Stabilized PEX-a Tubing	1	7	coil	\$ 2,209.72