

see what Delta can do<sup>SM</sup>

## BATHROOM FAUCETS


- Trinsic™ Bath Collection
- Two Hole On Wall

### STANDARD SPECIFICATIONS:

- Max 1.2 gpm @ 60 psi, 4.5 L/min @ 414 kPa
- Single handle bathroom faucet for wall mount installation
- Cast brass body
- Control mechanism is the ceramic disc cartridge
- Rough-in R3510-WL required for installation

### WARRANTY

- Parts and Finish - Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to [www.deltafaucet.com](http://www.deltafaucet.com) for the complete details of our limited warranty.



▲ Designate proper finish suffix



### COMPLIES WITH:

- ASME A112.18.1/CSA B125.1
- NSF/ANSI/CAN 61 & 372
- EPA WaterSense®



ICC / ANSI A117.1

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or [www.deltafaucet.com](http://www.deltafaucet.com) for finish options and product availability.

DSP-L-T3559LF-WL Rev. G

### Delta Faucet Company

55 E. 111th Street, Carmel, IN 46280  
 350 South Edgeware Road, St. Thomas, ON N5P 4L1  
 © 2026 Delta Faucet Company