


Meridian MEDICINE CABINET




FEATURES/TYPICAL SPECIFICATIONS

- Recess or Surface Mount Installation
 - Wall Opening/Rough-in Dimensions (for recess applications): 14" x 24" x 4 1/4"
- Formed and welded flush design steel housing (WB/ST)
 - 1/8" thick float glass mirror with polished edges on housing back
 - Electrical knock-outs for wire connections (3 typical)
 - 22 gauge steel construction with white, heat cured, acrylic paint finish
- Frameless Mirror door
 - 5/32" thick float glass mirror door front with 1/2" beveled edges, 4 sides
 - 3/32" float glass mirror door back with polished edges
 - 24 gauge steel door back with white, heat cured, acrylic paint finish.
- 170° euro hinge with soft-close mechanism (HG02) (2 typical)
- Reversible for left-hand or right-hand door swing
- 3/16" thick float glass shelves, adjustable (ADJ) (2 typical)
- 120 V GFCI dual receptacle, tamper resistant per NEC code - section 406.11 (1 typical)
- Snap-Fit shelf supports (20 typical)
- Includes installation hardware
- Standard Pallet Quantity of 21 units

Finishes:

Housing: PT01—Basic White
 Mirror: 1/2BVL-1/2" Bevel Edge
 Frame: Frameless



NOTE: Surface mount installation requires a Surface Mount Kit, 760024 (not included)

		Dimensions In Inches									
Model #	Description	A	B	C	D	E	F	G	H	J	K
704301	MEDCAB 1DR 15X25 FMLS WB/ST	15 5/8	25 5/8	1	5	13 1/2	3/4	15	23 1/2	3/4	1/16

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date