



Safety Data Sheet

May be used to comply with

OSHA's Hazard Communication Standard 29 CFR 1910.1200.

This standard must be consulted for specific requirements.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: ProPEX Grease
Product Models: 49-08-2400

Drawing Number: 58-97-1280
Issue Date: March 2015
Supersedes Date: November 2011

Milwaukee Electric Tool Corporation
13135 West Lisbon Road
Brookfield, Wisconsin 53005
www.milwaukeetool.com

Company Phone Number: 262-781-3600 or
1-800-729-3878
Emergency Contact Number: 1-800-424-9300
Chemtrec: United States only

Recommended intended purpose to be used as a lubricant.

SECTION 2: HAZARDS IDENTIFICATION

Health	Environmental	Physical
Eye Irritation: No classified hazards	Acute Toxicity: No classified hazards	Flammable liquid: No classified hazards
Skin Irritation: No classified hazards	Chronic Toxicity: No classified hazards	
Skin Sensitisation: Category 1		
Acute Toxicity, Oral: No classified hazards		
Acute Toxicity, Inhalation: No classified hazards		

GHS Label



Warning

Hazard Statements	Precautionary Statements
May cause eye irritation	IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. IF eye irritation persists: get medical attention/advice.
May cause allergic skin reaction	Contaminated work clothing should not be allowed out of the work place. Wear protective gloves/clothing/eye protection/face protection IF ON SKIN: wash with plenty of soap and water IF SKIN irritation or rash occurs call and get medical advice/attention Wash contaminated clothing before reuse
May be harmful if swallowed	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.

May be harmful if inhaled	IF INHALED: call a POISON CENTER or doctor/physician if you feel unwell.
May cause allergic skin reaction	Avoid breathing, dust/fumes/gas/mist/vapors/spray.

Classified Hazards

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200. This SDS contains valuable information for the safe handling and proper use of this product. Save this SDS for future reference.

Other Hazards

None known

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Components listed in this section may contribute to the potential hazards associated with exposure to the concentrate. The product may contain additional non-hazardous or trade-secret components.

Chemical characterization

Lubricating grease: thickening agent, additives and solid lubricants in highly-refined mineral oil

Chemical Name	CAS #	Concentration ¹
Petrolatum	8009-03-8	30~40
Triethanolamine	102-71-6	<1
Molybdenum Disulfide	1317-33-5	50~60
Mineral Oil	Trade Secret	5~10
Lubricating Additives	Trade Secret	1~5
Note: This product has been evaluated and does not require any hazard warning label under the OSHA Hazard Communication Standard.		
¹ All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume		

SECTION 4: FIRST AID MEASURES

EYE CONTACT:

Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. If symptoms persist, contact a physician.

SKIN CONTACT:

Remove product from the skin by washing with a mild soap and water. Contaminated clothing should be removed to prevent prolonged exposure. If symptoms of exposure persist, contact physician. If product is injected into or under the skin, seek treatment immediately. (see Note to Physician)

INHALATION:

If signs or symptoms of overexposure occur, remove the person to fresh air. If symptoms persist, seek medical attention.

INGESTION:

First aid is not normally required; however, if symptoms of ingestion persist, seek medical attention.

NOTE TO PHYSICIAN:

When using high-pressure equipment, injection of product under the skin can occur. In this case, the casualty should be sent immediately to hospital. Do not wait for symptoms to develop. High-pressure hydrocarbon injection injuries may produce substantial necrosis of underlying tissue despite an innocuous appearing external wound. These injuries often require extensive

emergency surgical debridement and all injuries should be evaluated by a specialist in order to assess the extent of injury. Early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

SECTION 5: FIRE FIGHTING MEASURES

NFPA 704 Hazard Class

No Data

HMIS



0 (Minimal)
1 (Slight)
2 (Moderate)
3 (Serious)
4 (Severe)

EXTINGUISHING MEDIA:

In accordance with NFPA guidance, dry chemical, foam, or CO2 fire extinguishers are all acceptable. Note that while water fog extinguishers are also acceptable, **DO NOT** apply a direct stream of water onto burning product because it may cause spreading and increase fire intensity.

UNUSUAL FIRE & EXPLOSION HAZARDS:

No further data known.

FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Emergency responders in the danger area should wear bunker gear and self-contained breathing apparatus for fires beyond the incipient stage. See Section 8 of the MSDS for other PPE to be worn as conditions warrant.

See Section 9 for Flammable Properties including Flash Point and Flammable (explosive) limits.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Clean-Up Measures:

Important: As with any spill or leak, before responding ensure that you are familiar with the potential hazards and recommendations of the MSDS. Appropriate personal protective equipment must be worn. See Section 8 of this MSDS for PPE recommendations.

If possible, safely contain the spill with dikes or other spill response equipment appropriate for petroleum or organic material releases. Take measures to prevent spreading of product. Note that while product will ignite it will not readily burn. However, as a precaution eliminate ignition sources. Prevent from entering sewers or waterways. Large volumes may be transferred to an appropriate container for proper disposal. Small volumes or residues may be soaked up with absorbents. Spill response materials should be collected for proper disposal.

SECTION 7: HANDLING AND STORAGE

HANDLING:

As with any industrial chemical, handle the product in a manner that minimizes exposure to practicable levels. Prior to handling, consult Section 8 of this MSDS to evaluate personal protective equipment needs. Open containers slowly to relieve any pressure. Follow all other standard industrial hygiene practices.

Empty containers may contain product residue. All safety precautions taken when handling this product should also be taken when handling empty drums and containers. Keep containers closed when not in use.

Product residue in empty containers is combustible but will not readily burn. NOTE however, that excessive heating or cutting of empty containers may create an ignition source sufficient to start a fire and in extreme cases, cause an explosion.

STORAGE:

Protect product quality by storing indoors and away from extreme temperatures. Close all containers when not in use.

SPECIAL COMMENTS:

No further data known.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Selection of personal protective equipment should be based upon the anticipated exposure and made in accordance with OSHA's Personal Protective Equipment Standard found in 29 CFR 1910 Subpart I. The following information may be used to assist in PPE selection.

Ingredient	OSHA PEL	ACGIH TLV	California Prop 65 Reg. Y/N	IARC/NTP Y/N
Petrolatum	Not established	Not established	N	N
Triethanolamine	TWA 5mg/m ³ *	TWA 5mg/m ³ *	N	N
Molybdenum Disulfide	TWA 3mg/m ³ *	TWA 3mg/m ³ *	N	N
Mineral Oil	TWA 5mg/m ³ *	TWA 5mg/m ³ *	N	N
Lubricating Additives	Not established	Not established	N	N
Note: This product has been evaluated and does not require any hazard warning label under the OSHA Hazard Communication Standard.				
* As oil mist, if generating				

EYE PROTECTION

Wear eye protection appropriate to prevent eye exposure. Where splashing is not likely, chemical safety glasses with side shields are recommended. Where splashing may occur, chemical goggles or full face shield is recommended.

SKIN PROTECTION:

Gloves are not normally needed during normal conditions of use. If health effects are experienced, oil or chemical resistant gloves such as butyl or nitrile are recommended.

Where splashing or soaking is likely, wear oil or chemical resistant clothing to prevent exposure.

RESPIRATORY PROTECTION:

A respirator may be worn to reduce the exposure to dust. Select a NIOSH/MSHA approved respirator appropriate for the type and physical character of the airborne material. A self-contained breathing apparatus is recommended in all situations where airborne contaminant concentration has not been confirmed to be below safe levels. Respirator use should comply with the OSHA Respirator Protection Standard found in CFR 1910.134.

ENGINEERING CONTROLS:

Normal general ventilation is expected to be adequate. It is recommended that ventilation be designed in all instances to maintain airborne concentrations at lowest practicable levels. Ventilation should at a minimum, prevent airborne concentrations from exceeding any exposure limits listed in Section 2 of this MSDS.

The user may wish to refer to 29 CFR 1910.1000 (d) (2) and the ACGIH "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices" (Appendix C) for the determination of exposure limits of mixtures. An industrial hygienist or similar professional may be consulted to confirm that the calculated exposure limits apply.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Data represent typical values and are not intended to be specifications. NA=Not Applicable; ND=Not Determined

Physical state:	Semi-Solid	Flammability (solid, gas):	NA
Colour:	Dark Gray	Upper Explosive Limits (vol % in air):	NA
Odor:	Oil Odor	Lower Explosive Limits (vol % in air):	NA
Odor Threshold:	ND	Vapor pressure:	NA
pH:	NA	Vapor density:	NA
Melting/Freezing Point:	NA	Relative density:	1.45
VOC Content:	NA	Solubility:	Insoluble
Boiling Point:	NA	Partition Coefficient:	NA
Flash Point:	200°C	Auto-ignition Temperature:	NA
Evaporation Rate:	ND	Decomposition Temperature:	NA
Specific Gravity:	ND	Viscosity:	ND

SECTION 10: STABILITY AND REACTIVITY

INCOMPATIBLE MATERIALS:

This product is incompatible with strong acids.

DECOMPOSITION PRODUCTS MAY INCLUDE:

Thermal decomposition products are dependent on combustion conditions. A complex mixture of airborne solid, liquid, particulates and gasses may evolve when the material burns.

CONDITIONS TO AVOID:

Avoid contact with incompatible materials and exposure to extreme temperatures.

POLYMERIZATION:

This product is not expected to polymerize.

CHEMICAL STABILITY:

This product is stable.

REACTIVITY:

Stable under normal ambient and anticipated conditions of use.

SECTION 11: TOXICOLOGY INFORMATION

LIKELY ROUTES OF EXPOSURE: Inhalation, Eye and Skin contact

ACUTE SYMPTOMS AND EFFECTS:

Inhalation:	No further toxicological data known
Eye contact:	No further toxicological data known
Skin contact:	No further toxicological data known
Ingestion:	No further toxicological data known

OTHER:

No further data known.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION:

This product has not been evaluated for ecotoxicity. As with any industrial chemical, exposure to the environment should be prevented and minimized wherever possible.

TOXICITY:

No data available

PERSISTENCE AND DEGRADABILITY (BIOPERSISTENCY & BIODEGRADABILITY):

The degree of biodegradability and persistence of this product has not been determined.

POTENTIAL OF BIOACCUMULATION:

No data available

MOBILITY IN SOIL:

No data available

OTHER ADVERSE EFFECTS:

No data available

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Ensure that collection, transport, treatment, and disposal of waste product, containers and rinsate complies with all applicable laws and regulations. Note that use, mixture, processing, or contamination of the product may cause the material to be classified as a hazardous waste. It is the responsibility of the product user or owner to determine at the time of disposal, whether the product is regulated as a hazardous waste.

SECTION 14: TRANSPORT INFORMATION

DOT HAZARDOUS MATERIAL INFORMATION:

Not otherwise DOT regulated.

SECTION 15: REGULATORY INFORMATION

FEDERAL REGULATIONS:**SARA 313:**

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Clean Water Act / Oil Pollution Act:

This product contains mineral oil and is subject to regulation by Section 311 of the Clean Water Act and the Oil Pollution Act. Releases of the product into or leading to surface waters must be reported to the National Response Center at 1-800-424-8802.

CERCLA Reportable Quantity:

Any components listed below have been assigned a reportable quantity (RQ) by the Federal EPA. Releases of the product into the environment that exceed the RQ for a particular component must be reported to the National Response Center at 1-800-424-8802.

Toxic Substance Control Act:

The components of this product are listed on the TSCA Inventory.

Ozone Depleting Substances:

This product contains no ozone depleting substances as defined by the Clean Air Act.

Hazardous Air Pollutants:

Any components listed below are defined by the Federal EPA as hazardous air pollutants.

STATE REGULATIONS:

This product contains mineral oil, and as used, may be regulated by the state used oil regulations. Check with the appropriate state agency to determine whether such a regulation exists.

No further data known.

SECTION 16: OTHER INFORMATION

ABBREVIATIONS:

TSCA Toxic Substance Control Act
ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous
OSHA Occupational Safety and Health
IARC/NTP International Agency for Research on Cancer/National Toxicology Program
SARA Superfund Amendments and Reauthorization Act of 1986
ACGIH American Conference of Governmental Industrial Hygienists
NIOSH/MSHA National Institute for Occupational Safety Health/
 Mine Safety and Health Administration
WHMIS Workplace Hazardous Materials Information System

Prepared by: Milwaukee Electric Tool Corporation

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. **MILWAUKEE ELECTRIC TOOL CORPORATION** makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereto. All risks associated with product use are assumed by the user.