



**Suggested Specification**

When retrofitted to either the PG8AC or P8AM, the PWEBQ bottle filler has independent contactless activation and laminar flow. VersaFiller alcove and cabinet shall be stainless steel. Key plastic components contain Freshshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew.

QUASAR bottle filler shall have UV-C LED treatment at the dispense point, which disinfects the water while it is being dispensed. UV-C LED also cycles on periodically to keep the dispense point sanitized between dispenses.

When retrofitted to either the PG8AC or P8AM the VersaFiller models satisfy ANSI A117.1 and ADA requirements when properly installed. Units also meet guidelines for children's accessibility providing the floor to bubbler orifice height is 30 inches and proper clear floor space is provided for frontal approach. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

<b>Features:</b>	<ul style="list-style-type: none"> <li>Contactless QUASAR with mercury-free UV-C LED treatment at the dispense point</li> <li>Built-in 100 micron strainer stops particles before they enter the waterway</li> <li>Waterways are lead-free in materials &amp; construction</li> <li>Heavy duty galvanized steel frame</li> <li>Contactless activation bottle filler with programmable auto shut off</li> </ul>
	<ul style="list-style-type: none"> <li>Ample space within the bottle filler cabinet to add filtration, including all OASIS filters</li> <li>Access filters through the top of the bottle filler for clean and easy replacement with Tilt 'N Tether</li> <li>Built-in filter monitor and bottle counter</li> <li>Logos permanently formed into the alcove and stainless steel wrapper</li> <li>LED lighted alcove</li> <li>Surface mount frame assembly</li> </ul>

<b>Filtration:</b>	Utilizes existing filtration if applicable. Option to add filtration to top of bottle filler.
<b>Power:</b>	115 Volts, 60 Hz
<b>Activation By:</b>	Contactless Sensor
<b>Mounting Type:</b>	Wall Mounted
<b>Chilling Option:</b>	Utilizes existing refrigeration system if applicable
<b>Full Load Amps</b>	0.4 amps
<b>Rated Watts</b>	25
<b>Approx. Net Weight</b>	17 lbs
<b>Installation Location:</b>	Indoor

MODEL: \_\_\_\_\_ QTY: \_\_\_\_\_

PROJECT: \_\_\_\_\_

CONTACT: \_\_\_\_\_

NOTES: \_\_\_\_\_

APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_

QUASAR ELECTRONIC RETROFIT BOTTLE FILLING STATION KIT, NON-REFRIGERATED  
**MODEL PWEBQ**



Ships in one box.

**Installation**

- The PWEBQ VersaFiller is designed to retrofit existing OASIS PG8AC and P8AM pressure cooler models. Units with optional glass fillers must have the glass filler disconnected and removed.
- Prior to rough-in consult with local, state, and federal codes for proper mounting height.
- Shipped with complete instructions and wall mounting brackets.

**Finishes**

- Standard cabinet finish: Stainless steel

**Limited 1-Year Warranty**

(Continental limits of the United States and Canada)  
One year on bottle fillers and electrical components. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

**Export Warranty**

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

**Certifications/Compliance**

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



Specifications subject to change without notice



# QUASAR ELECTRONIC RETROFIT BOTTLE FILLING STATION KIT, NON-REFRIGERATED **MODEL PWEBQ**

## Accessories



### Elkay® Adapter Gasket

OASIS Item #041533-001

- Elkay Adapter Gasket is necessary to complete installation if retrofitting to an Elkay® fountain



### OASIS VersaFilter III & Remedi Universal Retrofit Kit

OASIS Item #41253-002

- Add dual filtration to your unit - retrofit into all OASIS fountains and bottle fillers. VersaFilter III certified to NSF/ANSI 42 and 53 for lead, cyst, Particulate Class I, chlorine, taste and odor reduction to 4,750 gallons.



[View all filters and accessories](#)



QUASAR ELECTRONIC RETROFIT BOTTLE FILLING STATION KIT, NON-REFRIGERATED  
**MODEL PWEBQ**

