



QUASAR ELECTRONIC RETROFIT BOTTLE FILLING STATION KIT, NON-REFRIGERATED, DUAL FILTRATION MODEL PWF2EBQ

Suggested Specification

When retrofitted to either the PG8AC or P8AM, the PWF2EBQ bottle filler has independent contactless activation and laminar flow. Versa-Filler alcove and cabinet shall be stainless steel. Key plastic components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew.

QUASAR bottle filler shall have UV-C LED treatment at the dispense point, which disinfects the water while it is being dispensed. UV-C LED also cycles on periodically to keep the dispense point sanitized between dispenses.

When retrofitted to either the PG8AC or P8AM the VersaFiller models satisfy ANSI A117.1 and ADA requirements when properly installed. Units also meet guidelines for children's accessibility providing the floor to bubbler orifice height is 30 inches and proper clear floor space is provided for frontal approach. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

Features:	• Contactless QUASAR with mercury-free UV-C LED treatment at the dispense point
	• Built-in 100 micron strainer stops particles before they enter the waterway
	• Waterways are lead-free in materials & construction
	• Heavy duty galvanized steel frame
	• Contactless activation bottle filler with programmable auto shut off
	• Filters located in top bottle filler for easy filter replacement with Tilt 'N Tether
	• Access through the top of the bottle filler for clean and easy replacement of filters with Tilt 'N Tether
	• Built-in filter monitor and bottle counter
	• Logos permanently formed into the alcove and stainless steel wrapper
	• LED lighted alcove
• Surface mount frame assembly	

Filtration:	VersaFilter III is Certified to NSF/ANSI 42 and 53 for lead, cyst, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons and Remedi Filter.
--------------------	---

Power:	115 Volts, 60 Hz
---------------	------------------

Activation By:	Contactless Sensor
-----------------------	--------------------

Mounting Type:	Wall Mounted
-----------------------	--------------

Chilling Option:	Utilizes existing refrigeration system if applicable
-------------------------	--

Full Load Amps	0.4 amps
-----------------------	----------

Rated Watts	25
--------------------	----

Approx. Net Weight	17 lbs
---------------------------	--------

Installation Location:	Indoor
-------------------------------	--------

MODEL: _____ QTY: _____

PROJECT: _____

CONTACT: _____

NOTES: _____

APPROVAL: _____ DATE: _____



Ships in one box.

Installation

- The PWF2EBQ VersaFiller is designed to retrofit existing OASIS PG8AC and P8AM pressure cooler models. Units with optional glass fillers must have the glass filler disconnected and removed.
- Prior to rough-in consult with local, state, and federal codes for proper mounting height.
- Shipped with complete instructions and wall mounting brackets.

Finishes

- Standard cabinet finish: Stainless steel

Limited 1-Year Warranty

(Continental limits of the United States and Canada)
One year on bottle fillers and electrical components. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



Specifications subject to change without notice



QUASAR ELECTRONIC RETROFIT BOTTLE FILLING STATION KIT, NON-REFRIGERATED, DUAL FILTRATION **MODEL PWF2EBQ**

Accessories



Elkay® Adapter Gasket

OASIS Item #041533-001

- Elkay Adapter Gasket is necessary to complete installation if retrofitting to an Elkay® fountain



OASIS VersaFilter III Replacement Cartridge

OASIS Item #041145-001

- Certified to NSF/ANSI 42, 53 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



OASIS Remedi Replacement Cartridge

OASIS Item #037406-101

- Remedi filter utilizes the principle of electro-adhesion, capable of removing a wide range of water borne contaminants including bacteria, cysts, viruses and some heavy metals.



[View all filters and accessories](#)



QUASAR ELECTRONIC RETROFIT BOTTLE FILLING STATION
KIT, NON-REFRIGERATED, DUAL FILTRATION
MODEL PWF2EBQ

