



# VERSACOOLER™ SINGLE DRINKING FOUNTAIN, CONTACTLESS, REFRIGERATED, VERSAFILTER III FILTER MODEL PGF8ACT-FVF

## Suggested Specification

Model PGF8ACT-FVF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Shall have infrared sensor to activate the flow of water for the cooler. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be greystone on galvanized steel or sandstone powder coated or brushed stainless steel. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



<b>Features:</b>	• Built-in 100 micron strainer stops particles before they enter the waterway
	• Waterways are lead-free in materials & construction
	• Flexible and one-piece water saver bubbler infused with silver-based antimicrobial additive
	• Stainless steel top and heavy duty galvanized steel frame
	• High efficiency cooling system
	• Infrared sensor activation
	• Includes integral self-scouring waste drain
	• External access to stream height adjustment
	• External access to thermostat with tool activated OFF position

**Filtration System:** OASIS VersaFilter III, certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.

<b>Power:</b>	115 Volts, 60 Hz
<b>Activation By:</b>	Contactless activation
<b>Mounting Type:</b>	Wall Mounted
<b>Chilling Option:</b>	8.0 gph*
<b>Full Load Amps</b>	5.0 amps
<b>Rated Watts</b>	500
<b>Approx. Net Weight</b>	64 lbs
<b>Installation Location:</b>	Indoor

**Ships in one box.**

### Installation

- Prior to roughing in, consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

### Finishes

- Standard: Greystone powder coat on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

### Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system. Bottle fillers, fountains, and electrical components are warranted for 12 months. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

### Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

### Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

MODEL: \_\_\_\_\_ QTY: \_\_\_\_\_  
 PROJECT: \_\_\_\_\_  
 CONTACT: \_\_\_\_\_  
 NOTES: \_\_\_\_\_  
 APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_



**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



Specifications subject to change without notice



# VERSACOOLER™ SINGLE DRINKING FOUNTAIN, CONTACTLESS, REFRIGERATED, VERSAFILTER III FILTER **MODEL PGF8ACT-FVF**

## Accessories



### **Oasis VersaFilter III Replacement Cartridge**

OASIS Item #041145-001

- Certified to NSF/ANSI 42, 53 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



### **One piece chrome plated brass bubbler**

OASIS Item #036700-001

### **Push handle glass fillers**

OASIS Item # 029603-004



[View all filters and accessories](#)



VERSACOOLER™ SINGLE DRINKING FOUNTAIN,  
CONTACTLESS, REFRIGERATED, VERSAFILTER III FILTER  
**MODEL PGF8ACT-FV**

