



VERSACOOLER™ BI-LEVEL DRINKING FOUNTAIN, REFRIGERATED, PHARMACEUTICAL FILTER MODEL PGF8ACSL-FRX

Suggested Specification

Model PGF8ACSL-FRX shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Each fountain shall have four push pads to activate the manual flow of water for the cooler. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be greystone on galvanized steel or sandstone powder coated or brushed stainless steel. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

Features:	• Universal design: high right or high left
	• Built-in 100 micron strainer stops particles before they enter the waterway
	• Waterways are lead-free in materials & construction
	• Flexible and one-piece water saver bubbler infused with silver-based antimicrobial additive
	• Stainless steel top and heavy duty galvanized steel frame
	• High efficiency cooling system
	• Four push pads
	• Includes integral self-scouring waste drain
	• External access to stream height adjustment on lower VersaCooler fountain
	• External access to thermostat with tool activated OFF position
• Mechanical activation	

Filtration System: OASIS Pharmaceutical Filter Certified to NSF/ANSI 42, 53, 372 and 401 for chlorine, taste, odor, particulate class 1, lead, cysts, 12 pharmaceuticals, and microplastics reduction to 725 gallons.

Power:	115 Volts, 60 Hz
Activation By:	Manual Activation
Mounting Type:	Wall Mounted
Chilling Option:	8.0 gph*
Full Load Amps	5.5 amps
Rated Watts	550
Approx. Net Weight	65 lbs
Installation Location:	Indoor



Ships in one box.

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Finishes

- Standard: Greystone powder coat on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system. Bottle fillers, fountains, and electrical components are warranted for 12 months. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

MODEL: _____ QTY: _____

PROJECT: _____

CONTACT: _____

NOTES: _____

APPROVAL: _____ DATE: _____



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



Specifications subject to change without notice



VERSACOOLER™ BI-LEVEL DRINKING FOUNTAIN, REFRIGERATED, PHARMACEUTICAL FILTER **MODEL PGF8ACSL-FRX**

Accessories



OASIS Pharmaceutical Replacement Cartridge

OASIS Item #041670-001

- Certified to NSF/ANSI 42, 53, 372 and 401 for chlorine, taste, odor, particulate class 1, lead, cysts, Atenolol, Bisphenol A, Carbamazepine, DEET (diethyltoluamide), Estrone, Ibuprofen, Meprobamate, Metolachlor, Naproxen, Nonyl phenol, Phenytoin and Trimethoprim, and microplastics reduction to 725 gallons.



One piece chrome plated brass bubbler

OASIS Item #036700-001



Cane apron

Greystone Finish, OASIS Item # 035174-001

Sandstone Finish, OASIS Item # 035174-002

Stainless Steel Finish, OASIS Item #035174-003

- ADA Compliant Apron is needed when water cooler is not installed in an alcove or with right and left wing walls. OASIS Apron is to provide the mandatory 27" to floor ADA requirement.

Push handle glass fillers

OASIS Item # 029603-004



[View all filters and accessories](#)



VERSACOOLER™ BI-LEVEL DRINKING FOUNTAIN,
REFRIGERATED, PHARMACEUTICAL FILTER
MODEL PGF8ACSL-FRX

