



VERSACOOLER™ VANDAL RESISTANT BI-LEVEL DRINKING FOUNTAIN, NON-REFRIGERATED, WITH VANDAL RESISTANT BUBBLER & ELECTRONIC BOTTLE FILLER, TOTAL PFAS FILTER

MODEL PGVFEFSL-BRB-FPF

Suggested Specification

Model PGV8FEFSL-BRB-FPF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Shall include the VersaFiller® with contactless activation and laminar flow; each fountain shall have a single vandal resistant push button to activate the manual flow of water for the cooler. Bottle Filler alcove and cabinet finish shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. andal Resistant water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. One-piece vandal resistant metal bubbler keyed into place to prevent vandalism. Cabinet finish shall be brushed stainless steel. Cabinet finish shall be brushed stainless steel. Cabinet shall have galvanized steel screens to prevent objects from being inserted into ventilation panels or underside of unit. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



- | | |
|------------------|---|
| Features: | <ul style="list-style-type: none"> · Universal design: high right or high left · Built-in 100 micron strainer stops particles before they enter the waterway · Waterways are Lead-Free in materials & construction · Vandal resistant metal water saver bubbler · Vandal resistant fasteners · Galvanized steel louver and bottom screens · High efficiency cooling system · Stainless steel top and heavy duty galvanized steel frame · Contactless activation bottle filler with programmable auto shut off · Includes integral self-scouring waste drain · External access to stream height adjustment on lower VersaCooler fountain · Filter located in top bottle filler for easy filter replacement with Tilt 'N Tether · Built-in filter monitor and bottle counter · Logos permanently formed into the alcove and stainless steel wrapper · LED lighted alcove |
|------------------|---|

Filtration System:	OASIS Total PFAS, certified to NSF/ANSI 42, 53, 372 and 401 for chlorine, taste, odor, particulate class 1, lead, cysts, Total PFAS, and microplastics reduction to 1,100 gallons.
Power:	115 Volts, 60 Hz
Activation By:	Contactless Sensor on Bottle Filler and Manual Activation on Fountain
Mounting Type:	Wall Mounted
Chilling Option:	Non-refrigerated
Full Load Amps	0.2 amps
Rated Watts	11
Approx. Net Weight	55 lbs
Installation Location:	Indoor

MODEL: _____ QTY: _____

PROJECT: _____

CONTACT: _____

NOTES: _____

APPROVAL: _____ DATE: _____

Ships in one box.

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Finishes

- Standard cabinet finish: Stainless steel

Limited 1-Year Warranty

(Continental limits of the United States and Canada)
One year on bottle fillers and electrical components. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



Specifications subject to change without notice



VERSACOOLER™ VANDAL RESISTANT BI-LEVEL DRINKING FOUNTAIN, NON-REFRIGERATED,
WITH VANDAL RESISTANT BUBBLER & ELECTRONIC BOTTLE FILLER, TOTAL PFAS FILTER

MODEL PGVFEBFSL-BRB-FPF

Accessories



OASIS Total PFAS Replacement Cartridge

OASIS Item #041668-001

- Certified to NSF/ANSI 42, 53, 372 and 401 for chlorine, taste, odor, particulate class 1, lead, cysts, Total PFAS, and microplastics reduction to 1,100 gallons.



Cane apron

Stainless Steel Finish, OASIS Item #035174-003

- ADA Compliant Apron is needed when water cooler is not installed in an alcove or with right and left wing walls. OASIS Apron is to provide the mandatory 27" to floor ADA requirement.



[View all filters and accessories](#)



VERSACOOLER™ VANDAL RESISTANT BI-LEVEL DRINKING FOUNTAIN, NON-REFRIGERATED, WITH VANDAL RESISTANT BUBBLER & ELECTRONIC BOTTLE FILLER, TOTAL PFAS FILTER

MODEL PGVFEBSL-BRB-FPP

