

A Full-Featured Family to Make Your Job Easier



The Intelligent Use of Water™
Leadership · Education · Partnerships · Products

At Rain Bird, we believe it is our responsibility to develop products and technologies that use water efficiently. Our commitment also extends to education, training and services for our industry and our communities.

The need to conserve water has never been greater. We want to do even more, and with your help, we can. Visit www.rainbird.com for more information about The Intelligent Use of Water™.

Rain Bird®
Rotors

Superior Performance,
Versatility, and Durability...
Ready for Any Application



Rain Bird Corporation
6991 E. Southpoint Rd.
Tucson, AZ 85756
Phone: (520) 741-6100
Fax: (520) 741-6522

Rain Bird Corporation
970 West Sierra Madre Ave.
Azusa, CA 91702
Phone: (626) 812-3400
Fax: (626) 812-3411

© 2023 Rain Bird Corporation

D42383

Rainbird.com

* Registered Trademark of Rain Bird Corporation



3500 | 5000 | Falcon® 6504 | 8500 Series



Whatever the residential or commercial application, Rain Bird Rotors have it covered.

Rain Bird Rotors set the standard for durability and reliable performance. There's a Rain Bird Rotor for every application—low pressure, steep slopes, high wind, non-potable water, even vandalism. Choose Rain Bird Rotors. Get the results you seek.

Quick Guide to Rotor Model Numbers



Note: Certain specifications are not available for some rotor series.

3500 ▶▶▶ 15' to 35' (4.6 m to 10.7 m)

5000 ▶▶▶ 25' to 50' (7.6 m to 15.2 m)

6504 ▶▶▶ 39' to 65' (11.9 m to 19.8 m)

8005 ▶▶▶ 39' to 81' (11.9 m to 24.7 m)

Radius of Throw

Feet 15 20 25 30 35 40 45 50 55 60 65 70 75 80

3500 Series

0.37 to 0.83 in/hr (9 to 21 mm/h)

25 to 55 psi (1.7 to 3.8 bar)

0.54 to 4.6 gpm (2.0 to 17.4 l/m) (0.12 to 1.04 m³/h)

4" (10.2 cm)

Shrub: 7" (17.8 cm)
4": 6 5/8" (16.8 cm)

1/2" NPT

shown with Plus Flow shut-off option

5000 Series

0.20 to 1.50 in/hr (5 to 37 mm/h)

25 to 65 psi (1.7 to 4.5 bar)

0.76 to 9.63 gpm (3.0 to 36.6 l/m) (0.17 to 2.19 m³/h)

Shrub: 4" (10.2 cm)
6" (15.2 cm)

Shrub: 7 3/4" (19.7 cm)
4": 7 7/8" (18.5 cm)
6": 9 5/8" (24.5 cm)

3/4" NPT

Falcon® 6504 Series

0.37 to 1.26 in/hr (9 to 32 mm/h)

30 to 90 psi (2.1 to 6.2 bar)

2.9 to 21.7 gpm (10.8 to 82.2 l/m) (0.66 to 4.93 m³/h)

4" (10.2 cm)

8 1/2" (21.6 cm)

1" NPT or BSP

8005 Series

0.48 to 1.23 in/hr (12 to 31 mm/h)

50 to 100 psi (3.5 to 6.9 bar)

3.8 to 36.3 gpm (14.4 to 137.4 l/m) (0.86 to 8.24 m³/h)

5" (12.7 cm)

10 1/8" (25.7 cm)

1" NPT or BSP

Standard Features

- Attached nozzle tree of six Rain Curtain™ Nozzles deliver superior performance
- Top-adjust arc adjustment requiring only a flathead screwdriver
- Optimized for short to mid-distance applications
- Quick check arc/fast forward
- Easily removable filter screen
- Dual action, positive stop wiper seal protects internals from debris and assures positive pop-up and retraction
- 3 year trade warranty

Options

- SAM Seal-A-Matic™** check valves prevent low head drainage and erosion



Standard Features

- Slip clutch left edge finder
- Self flushing port
- Standard and Low angle nozzles
- Rain Curtain nozzles
- 5 year warranty

Options

- Plus (PL) Flow shutoff** – “The Green Top.” Reduce downtime on jobs by flushing and nozzling rotors without running back and forth to the controller or valves
- PRS (R)** with flow optimizer technology. The 45 psi pressure regulator lowers water bills, provides exact flow of each rotor, equalizes lateral lines, and eliminates misting and fogging
- SAM Seal-A-Matic** check valve
- Stainless steel (SS)** riser helps deter vandalism on public turf areas (available on 4 and 6" models)
- Purple cover (NP)** for non-potable systems



Standard Features

- Ratcheting stem just like standard spray bodies
- 3-port, color-coded Rain Curtain nozzles for optimal long range, mid-range, and close-in watering
- Easy arc adjustment (part-circle model) through top of rotor from 40° to 360°
- SAM Seal-A-Matic check valve
- Heavy-duty, stainless steel retract spring ensures positive pop-down
- 5 year warranty

Options

- Stainless steel (SS)** riser helps deter vandalism on public turf areas
- Purple cover (NP)** for non-potable systems



Standard Features

- Vandal resistance
- Brass reinforced turret for increased side impact durability
- Non strippab le gear drive
- Memory Arc
- Part and Full Circle in one head
- Independent left and right edge adjustment
- SAM Seal-A-Matic check valve
- 3-port, color-coded Rain Curtain nozzles for optimal long-range, mid-range, and close-in watering
- 5 year warranty

Options

- Stainless steel (SS)** riser helps deter vandalism on public turf areas
- Purple cover (NP)** for non-potable systems




5000PRS Pressure Regulating System:

Savings That Add Up

The Problem

- Studies indicate that the average inlet water pressure in the U.S. is 73 psi, with many sites exceeding 100 psi.



- But when pressure exceeds the recommended level of 45 psi, rotor performance suffers and results in wasted water and money.




The Solution

- The Rain Bird Pressure Regulating Stem (PRS), is designed specifically to keep performance at optimal levels regardless of varying inlet pressure.
- PRS can provide significant water savings, cost savings, and improved performance vs. non-PRS systems.

The Proof

PRS Rotors Testing



The savings reaped per rotor can be multiplied across an entire system, resulting in significant differences financially and in gallons of water used.

**Theoretical Lifetime Savings is normalized water savings based on EPA WaterSense estimate of average US household/outdoor water use, an average cost/1,000 gallons of water in the US and an average product lifespan of 7 years. The totals are theoretical. Actual water savings will vary based on conditions. For more information on Rain Bird® PRS technology, visit PRS.rainbird.com.*

