

CAPACITORS

TURBO 200 FAMILY CAPACITORS

Turbo200 MINI

The Turbo MINI motor-run capacitor has a capacitance range of 2.5 - 15 μ F, and is rated for up to 440V. Permanent replacement for up to fourteen popular "fan-sized" values.



PART NO	DESCRIPTION
439102	Turbo200 MINI Capacitor

Turbo200 MINI Oval

Replaces 2.5 μ F, 3 μ F, 4 μ F, 5 μ F, 7.5 μ F, 10 μ F, 12.5 μ F and 15 μ F capacitors for both 370 and 440V applications.



PART NO	DESCRIPTION
PD439104	Turbo200 MINI Capacitor - Oval

Turbolytic50 Start Capacitor

The Turbolytic50 motor-start capacitor has a capacitance range of 21-324 μ F, and is rated for use at 125-330V.



PART NO	DESCRIPTION
TurboLytic50	Universal Motor Start Capacitor - 302/330 MFD

TurboMeter

See the dual values develop simultaneously on the screen as you create the ratings needed.



PART NO	DESCRIPTION
439103	TurboMeter (DSC)

CONTACTORS

CONTACTORS – SINGLE POLE

Contactors – PROTECH/OEM (Single Pole)



Qualified OEM replacements for Rheem, Ruud, and WeatherKing equipment when selected from unit parts lists.



PART NO	COIL VOLTAGE (VAC)	MOTOR FLA RATING @230V (A)	MOTOR LRA RATING @230V (A)	RESISTIVE RATING @230V (A)	MOTOR FLA RATING @460V (A)	MOTOR LRA RATING @460V (A)	RESISTIVE RATING @460V (A)	MOTOR FLA RATING @575V (A)	MOTOR LRA RATING @575V (A)	RESISTIVE RATING @575V (A)	AUXILIARY CONTACTOR
42-25101-01	24	32	180	40	32	150	40	32	120	40	—
42-25101-03	24	40	240	50	40	200	50	40	160	50	—
42-25101-07	0,120	32	180	40	32	150	40	32	120	40	—
42-25101-02	208,230	32	180	40	32	150	40	32	120	40	—
42-25101-04	208,230	40	240	50	40	200	50	40	160	50	—

Contactors – Wholesale (Single Pole)

- Competitively sourced to bring you the quality contactors at the best possible price!
- Includes manual test switch; minimum two quick connect shunt terminals at each power terminal

PART NO	COIL VOLTAGE (VAC)	MOTOR FLA RATING @230V (A)	MOTOR LRA RATING @230V (A)	RESISTIVE RATING @230V (A)	MOTOR FLA RATING @460V (A)	MOTOR LRA RATING @460V (A)	RESISTIVE RATING @460V (A)	MOTOR FLA RATING @575V (A)	MOTOR LRA RATING @575V (A)	RESISTIVE RATING @575V (A)	AUXILIARY CONTACTOR
425066	24	30	180	40	30	150	40	30	120	40	—