

Power Threading Machines



Model 300 Power Drive Complete

- RIDGID Speed Chuck.
- Reversible 1/2 HP Universal Motor.
- Recessed On/Off/Reverse Switch.
- Ideal For Use With RIDGID Roll Groovers.

Specifications

- Motor – 1/2 HP Single Phase, Universal.
- Switch – Heavy-duty For/Off/Rev and Integral Foot Switch.
- Chuck – Speed Chuck with Replaceable Rocker-Action Jaws.
- Spindle Speed – 38 RPM (57 RPM Available).
- Rear Centering Device – Cam-Action Turns With Chuck.
- Support Bar – Heavy-Duty.

Standard Equipment.

- 97065 – 811A 1/8" - 2" NPT, Quick Opening, RH.
- 47745 – 1/2" - 3/4" Universal Alloy Die Set.
- 47750 – 1" - 2" Universal Alloy Die Set.
- 42370 – Model 360 1/8"-2" Full Floating, Self Centering Cutter.
- 68815 – Carriage with No. 312 Lever.
- 42575 – #32 Transporter (for Power Drives and Tristand Vises).
- 42365 – Reamer.
- 42360 – 1206 Stand.
- 10883 – Oiler w/1 Gal. Premium Thread Cutting Oil.
- 22638 – Clip-On Tool Tray.
- 41855 – 300 Power Drive, 115V 50/60Hz.



Model 32 Transporter



Catalog No.	Model No.	Pipe Threading Capacity		Rod Threading Capacity		Spindle Speed	Voltage	Frequency	Max. Geared Threader Capacity		Weight	
		in.	mm	in.	mm				in.	mm	lb.	kg
15682	300 Complete	1/8 - 2	3 - 50	1/4 - 2	6 - 50	38 RPM	115	50 - 60	6	150	212	96.2
15722	300 Complete	1/8 - 1 1/4	3 - 31	1/4 - 1 1/2	6 - 40	57 RPM	115	50 - 60	6	150	212	96.2
97415	300A Complete*	1/8 - 2	-3 - 50	1/4 - 1 1/2	-	38 RPM	230	50 - 60	6	-150	202	91.6
97420	300A Complete*	1/8 - 2	-3 - 50	1/4 - 2	-	38 RPM	230	50 - 60	6	-150	202	91.6

Other voltages available upon request. Export machines equipped with special power cord sets.
 *300A includes automatic oiling



See page 4.12