



# Veritek® Single Threshold Shower Floors With Fit-Flo™ Drain

Manufactured from Veritek®  
(See page 2 for detailed information.)


WARRANTY  
Limited Lifetime – Residential  
Limited 5-year – Commercial

## FEATURES


- Will not mold or mildew, no grout to clean.
- Coordinates with other Swanstone or Veritek® products.
- Pebbled, slip-resistant surface.
- Made of Veritek® with no surface coating to chip or crack.

Model	Nominal Size	Rough-In Dimensions			
		A	B	C	D
R-3232	32" x 32"	32-3/8"	32-3/16"	16-3/16"	16-3/16"
R-3248	32" x 48"	48-3/8"	32-3/16"	24-3/16"	16-3/16"
R-3260	32" x 60"	60-3/8"	32-3/16"	30-3/16"	16-3/16"
R-3442	34" x 42"	42-3/8"	34-3/16"	21-3/16"	17-3/16"
R-3448	34" x 48"	48-3/8"	34-3/16"	24-3/16"	17-3/16"
R-3454	34" x 54"	54-3/8"	34-3/16"	27-3/16"	17-3/16"
R-3460	34" x 60"	60-3/8"	34-3/16"	30-3/16"	17-3/16"
R-3636	36" x 36"	36-3/8"	36-3/16"	18-3/16"	18-3/16"
R-4236	42" x 36"	36-3/8"	42-3/16"	18-3/16"	20-3/16"
R-4242	42" x 42"	42-3/8"	42-3/16"	21-3/16"	21-3/16"

Model	A	B	C	D
R-3232	32"	32"	16"	16"
R-3248	48"	32"	24"	16"
R-3260	60"	32"	30"	16"
R-3442	42"	34"	21"	17"
R-3448	48"	34"	24"	17"
R-3454	54"	34"	27"	17"
R-3460	60"	34"	30"	17"
R-3636	36"	36"	18"	18"
R-4236	36"	42"	18"	20"
R-4242	42"	42"	21"	21"



IMPORTANT: Rough-in dimensions are provided for reference only. You must measure the actual shower floor and check local building code requirements before construction of the stud wall.



## SPECIFICATIONS

### Single Threshold Shower Floors With Fit-Flo™ Drain

Model	Part	Nominal Size Dimensions	Ship Wt. Lb.	Ship FedEx	Carton Dims. In.	Cu. Ft.
R-3232	FFo3232MD	32" D x 32" W (813 mm x 813 mm)	32	-	38 x 37 x 10	9
R-3248	FFo3248MD	32" D x 48" W (813 mm x 1219 mm)	49	-	54 x 38 x 10	12
R-3260	FFo3260MD	32" D x 60" W (813 mm x 1524 mm) - Center drain	56	-	66 x 37 x 10	15
R-3442	FFo3442MD	34" D x 42" W (864 mm x 1067 mm)	46	-	48 x 40 x 10	12
R-3448	FFo3448MD	34" D x 48" W (864 mm x 1219 mm)	47	-	54 x 39 x 10	13
R-3454	FFo3454MD	34" D x 54" W (864 mm x 1372 mm)	55	-	60 x 40 x 10	14
R-3460	FFo3460MD	34" D x 60" W (864 mm x 1524 mm)	63	-	66 x 40 x 10	16
R-3636	FFo3636MD	36" D x 36" W (914 mm x 914 mm)	40	-	42 x 41 x 10	10
R-4236	FFo4236MD	42" D x 36" W (1067 mm x 914 mm)	44	-	47 x 42 x 10	12
R-4242	FFo4242MD	42" D x 42" W (1067 mm x 1067 mm)	53	-	48 x 48 x 10	14

## COLORS

- Solid Colors:**
- White (o10)
  - Bisque (o18)
  - Bone (o37)

Includes: One code-approved compression-molded Veritek® shower floor with molded-in Fit-Flo drain.

Packaging: Each floor packed in a rectangular carton.

## STANDARDS AND RATINGS

- American National Standard Institute—ANSI Z124.1.2
- International Association of Plumbing and Mechanical Officials (IAPMO)—Listed CSA Standard B45.5 by IAPMO
- Uniform Plumbing Code (UPC)

For a complete list of tests and results see the Technical Data Sheet.

## SUPPORT DOCUMENTS

Installation instructions available at [swanstone.com](http://swanstone.com).

## MAINTENANCE AND CLEANING INFORMATION

Clean regularly with common household liquid cleaners and a sponge or soft cloth. For hard water stains, scale removers can be used. If necessary, abrasive cleaners can be used with a nylon brush or pad to remove build up on the shower floor surface. **Do not** use a metal-scouring pad or a wire brush, as it will damage the surface. **Do not** use "leave on" cleaning products, such as automatic spray shower cleaners. Prolonged contact with harsh chemicals could have an adverse reaction over time and discolor surfaces. **Do not** use cleaning agents that caution use on acrylic, polyester or plastics.

**MADE IN USA**

SHOWER FLOORS